

ADDENDUM NO. 3

Date: August 26, 2014
Project: City of Tuscaloosa
City Walk at University Place and Forest Lake
Project No. A12-1413/A12-0993
Bid Date: **Thursday, August 28, 2014**
9:00 a.m. local time
Narashino Conference Room in City Hall

The following changes, additions, clarifications, and/or deletions are hereby made part of the Contract Documents for the project referenced above as fully and completely as if the same were set forth fully therein:

1. Construction Plans:
 - a) Sheet C3.3b.0 – modification to Section 03

2. Bidder Questions:
 - a) Question: Clarification of Intent of Note 17 on Sheet I1.3?
Answer: Wiring from the flow sensor to the controller shall be in a separate conduit and not contained in a conduit with the other controller wire. The sensor wiring shall meet the flow sensor manufacturer's specifications. The contractor will be required to install a minimum of four feet of straight run pipe going into and coming out of the flow sensor. Based on other installations these straight sections of piping will reduce the potential of having false flow readings that can potentially turn off the system.

Attachments:

- Construction Plan Sheet C3.3b

RECEIPT OF ADDENDUM NO. 3

The following hereby acknowledges receipt of Addendum No. 3, dated August 26, 2014.

Complete the following and return by fax to (205) 759-1524 or scan and email to dmarcum@mcgiffert.com.


We are in receipt of Addendum No. 3 and fully understand the contents and our bid on the above referenced project submitted reflects the intent of this Addendum.

Contractor Name


*By: _____

Date: _____


* *Signature must be by person legally qualified to sign bid.*



Section 02
Scale: 3/4" = 1'-0"



Section 03
Scale: 3/4" = 1'-0"



Height	Width	Toe	Heel	"O" bars	"P" bars	"D" bars	"L" bars
3'-0"	0'-8"	0'-6"	1'-0"	# 4 @ 12"	# 4 @ 12"	# 4 @ 12"	4 # 4 bars
4'-0"	0'-8"	0'-6"	1'-7"	# 4 @ 12"	# 4 @ 12"	# 4 @ 12"	4 # 4 bars
5'-0"	0'-8"	0'-6"	2'-2"	# 4 @ 12"	# 4 @ 12"	# 4 @ 12"	4 # 4 bars
6'-0"	0'-8"	0'-8"	2'-5"	# 4 @ 12"	# 4 @ 12"	# 4 @ 12"	4 # 4 bars
7'-0"	0'-8"	1'-0"	2'-6"	# 4 @ 12"	# 4 @ 12"	# 4 @ 12"	4 # 4 bars
8'-0"	1'-0"	1'-0"	2'-8"	# 4 @ 12"	# 4 @ 12"	# 4 @ 12"	4 # 4 bars
9'-0"	1'-0"	1'-0"	3'-2"	# 4 @ 11"	# 4 @ 11"	# 4 @ 11"	5 # 4 bars
10'-0"	1'-0"	1'-2"	3'-7"	# 5 @ 12"	# 5 @ 12"	# 4 @ 11"	5 # 4 bars
11'-0"	1'-1"	1'-5"	4'-1"	# 5 @ 9"	# 5 @ 9"	# 4 @ 9"	6 # 6 bars
12'-0"	1'-2"	1'-6"	4'-7"	# 5 @ 8"	# 5 @ 8"	# 4 @ 8"	6 # 6 bars

- Notes:
1. All concrete shall be 4000 psi @ 28 days.
 2. All reinforcing steel shall be ASTM A 615 Grade 60.
 3. Provide 2" dia weep holes through the wall @ 10'-0" o.c.
 4. Provide vertical scored control joints @ 10'-0" o.c.

GENERAL NOTES

1. Any omissions or discrepancies between plans, details, and specifications shall be brought to the attention of the Architect or Engineer before bidding.
2. Contractor proposed changes to details must be clearly noted on the first sheet of all shop drawings.
3. Intersections of new and old construction illustrate interpretations of existing conditions. Before starting any construction, verify all existing conditions.

REINFORCING STEEL AND CONCRETE

1. All concrete work is to be in accordance with the "Building Code Requirements for Reinforced Concrete" (ACI 318-08).
2. All detailing is to be in accordance with "ACI Detailing Manual" SP-66.
3. Concrete Properties: See Schedule. All concrete must obtain 7 day strength of 70% of design strength. Concrete mixes may use up to 25% of cementitious weight as fly ash. Concrete mixes may use water reducers, accelerators or retarders with prior approval.
4. All steel reinforcement shall be of deformed bars of billet steel conforming to ASTM A615, Grade 60 in all concrete.
5. Minimum concrete cover for reinforcement:

Beam	1 1/2" outside of stirrups
Slabs and Joists	3"
Other surfaces	5/8"
Cast-in-Place Wall	2" - #6 and greater, 1-1/2" - #5 and smaller
Surfaces exposed to weather or soil	3/4"
Other surfaces	

Concrete Use	Design Strength	Min W/C Ratio	Slump Limits	Entrained Air Range	Weight	Notes:
All Concrete	4000 psi	n/a	3" to 5"	3% to 5%	150 pcf	Use HRWR

Barnett · Jones · Wilson, LLC
Structural Engineers Pett City & Tuscaloosa Alabama www.structeng.com



McGiffert and Associates, LLC
Civil Engineers
2814 STILLMAN BLVD. • P.O. BOX 20559
TUSCALOOSA, ALABAMA 35402-0559
WWW.MCGIFFERT.COM (205)759-1521 FAX (205)759-1524

REVISION		
DATE	DESCRIPTION	BY
8-24-14	Addendum #3	JCW

THIS DRAWING AND ALL INFORMATION SHOWN HEREON IS THE PROPERTY OF THE ENGINEER AND MAY NOT BE REPRODUCED OR USED WITHOUT WRITTEN CONSENT OF THE ENGINEER.
COPYRIGHT © 2013 MCGIFFERT AND ASSOCIATES, LLC

CITY OF TUSCALOOSA
CITY WALK AT UNIVERSITY PLACE & FOREST LAKE
CITY OF TUSCALOOSA PROJECT NO. A12-1413/A12-0993
WHITFIELD CREEK CROSSING

FILE NAME:	SCALE: AS SHOWN	DWG. No.	SHEET No.
DATE OF FIELD SURVEY:	PAGE:	DRAWN BY: JCW	C3.3b
JOB No. 13-2431	CHECKED BY: JCW		